Update on uBooNE DAQ development effort in LCC.

Gennadiy Lukhanin

Outline

- Jungo windriver
- Event building with SEB / Assembler
- CET build tools
- CSS V3.1.1
- Near-term plans

Jungo Windriver

- Jungo windriver is available thru UPS
  - does not depend on the hardware identification and can be shared over NFS across all SEBs
  - has two key components: 1) a generic PCIe driver for talking to FPGAs and 2) a client library with a software license key compiled into it
  - needs to be rebuild into a separate UPS product after each linux kernel update/upgrade
    - the build script is in /uboone/windriver/v11_00_00
  - is not loaded on startup; (need to automate)
    - ksu
    - . /uboone/setup
    - **setup windriver v11_00_00 -f Linux64bit+2.6-2.12 -q debug**
    - wdreg windrvr6 #(or nevispcie)
    - chmod a+rw /dev/windrvr6 #(or nevispcie)
  - had to modify a couple of headers to compile with gcc4.6.2



Event building with SEB / Assembler

- SEB processes generate event fragments of variable length into a queue from which they are sent over a socket connection to the assembler process, which coalesces them into complete events and writes into a file.
  - all 10 SEB processes are started with ~/development/uboonedaq/projects/tools/start-fake-sebs.sh on uboonedaq-seb-01
  - assemblerMain is started on uboonedaq-ebv
  - don't forget to setup your development environment on both seb-01 and evb machines
- Fragment send/receive data rates and fragment counts are posted to the ganglia online monitoring system
  - http://uboonedaq-evb.fnal.gov:8080/gweb

Ganglia screenshots









Plots show network activity, received data rates and received fragment rates monitored on the evb node.







Plots show network activity, sent data rates and sent fragment rates monitored on the seb10 node.

CET build tools

Build instructions:
https://cdcvs.fnal.gov/redmine/projects/uboonedaq/wiki/Setup-uboonedaq-for-development

CMakeLists.txt files follow all cmake rules and use time saving macros provided by the cetbuildtools package, which is available thru UPS and loaded by the setup_for_development script.

Uboone DAQ is using **git** for source control and does not provide any wrappers or change the interaction with the **git** repository. All **git** rules and commands are applicable. The *setup-development-source* script does "*git clone*" and "*git checkout cetcmake*".

Steps to recreate your development environment

0. mv development development002
1. mkdir ~/development
3. export UBOONEDAQ_HOME_DIR=${HOME}/development
4. source /uboone/setup_online.sh
5. setup-development-source
6. kinit lukhanin
7. setup-development-source
8. cd ${HOME}/development/build
9. source ../uboonedaq/projects/ups/setup_for_development –d
10. cmake -DCMAKE_INSTALL_PREFIX=${UBOONEDAQ_HOME_DIR}/11. install -DCMAKE_BUILD_TYPE=$CETPKG_TYPE -Dqualifier:STRING=$CETPKG_QUAL $CETPKG_SOURCE
11. make -j32
12. . ~/development/install/setup
13. setup uboonedaq v1_00_00 -q debug:e1
    - **Use highlighted commands for running previously compiled code.**

CSS V3.1.1

Data browser plugin shows data plots correctly from a database.



Alarms can trigger automatic actions such as sending email notifications and executing custom commands.



Web OPI interface allows viewing OPI pages in a web browser.

Near-term plans

- Define uboone specific data structures for encapsulating event fragments and events.
- Automate jungo driver loading during linux boot.
- Implement reading event fragments from a Nevis card.
  - need a short document describing the communication protocol for the Nevis card and front-end electronics.
- Add state machines to both SEB and assembler applications.
  - we have a first version implemented in the SMC compiler language.